



- NOTES:
- 1.0 PLATING:
- 1) Contact plating: brass Au3u"over 50-120u" Ni
 - 2) Contact solder area plating: brassAu 3u" over 50-120u" Ni
 - 3) Spring: SUS
 - 2.0 Rated voltage(Per Contact): 12 Volts
 - 3.0 Rated Current(Per Contact): 1A
 - 4.0 Insulation Resistance: 100M Ω minimum
 - 5.0 Dielectric Withstanding Voltage: 100V at 60HZ
 - 6.0 Contact Resistance: 30m Ω maximum before test and 60m Ω maximum after test at pogo pin working stroke
 - 7.0 Recommended Working Stroke&Force:
 - 1) Stroke: 0.8mm(Per Contact): 150gf/Max
 - 8.0 Mechanical life:
 - 1) Mechanical life: 10,000 Cycles Min
 - 9.0 Working Temperature Range: -30~85°

变号	变号
变号	变号
变号	变号

POMAGTOR
磁性连接—专业为您定制

深圳市泰科汉泽精密电子有限公司
Pomagtor Precision Electronics

变更说明	序号	变更描述	原因	设计者	日期	描述	料号	单位	2. 0*6. 2P060 PIN, 材质黄铜C3604	MM	绘图/日期	审核/日期	版本	比例
1	1						HY90-00097-001						A1	1:1
2	2													
3	3													