



- NOTES:
- 1.0 PLATING:
 - 1)Contact plating:brass Au3u"over 50u-120u" Ni
 - 2)Contact solder area plating: brassAu 3u" over50u-120u" Ni
 - 3)Spring: SUS
 - 2.0 Rated voltage(Per Contact): 5 Volts
 - 3.0 Rated Current(Per Contact): 1.0A
 - 4.0 Insulation Resistance: 100MΩ minimum
 - 5.0 Dielectric Withstanding Voltage:100V at 60HZ
 - 6.0 Contact Resistance:30mΩ maximum before test and 60mΩ maximum after test at pogo pin working stroke
 - 7.0 Recommended Working Stroke&Force:
 - 1)Stroke1.0mm(Per Contact); 60gf±20gf
 - 8.0 Mechanical life:
 - 1)Mechanical life: 10,000 Cycles
 - 9.0 Working Temperature Range: -30~-85°

模架号	模芯号
-----	-----
-----	-----

POMAGTOR
磁性连接—專業為您定制

深圳市泰科汉泽精密电子有限公司
Pomagtor Precision Electronics

变更说明	序号	变更描述	原因	设计者	日期	描述	料号	单位	1.8*4.75P000 PIN,黄铜C3604, 镀金3u	MM	绘图/日期	审核/日期	版本	比例
1	1	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	A1	1:1
2	2	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----
3	3	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----