Manner of packing			REV'	ECN NO'	LOCAS'	DESCRIPTION	DATE	DESIGN
PE Bag	1.0K		A0			NEW	2012.02.13	譚立強



PCB LAYOUT

Layout Tolerance:±0.20mm

NOTE:

1.Material

.Plunger: Brass

2.Plating

.Contact surface:1u" minimum Au over 80~100u" Ni

3.Electrical

.Rated Current & Voltage: DC 12V; AC 1~1.65A,24H

.Contact Resistance: 25mΩ maximum

4.RoHS COMPLIED PROUCT.

5.Elasticity:Stroke 0mm:10gfStroke 0.25mm:50gf Stroke 2.90mm (or fully compressed):100-150gf

6.Life (Million):stroke range Max0.5~4mm,根据Pin的总类不一样Max. Stroke 10000次 Touch down后重量变化 0.5gf以内Creep变形最小化

7.Temperature: -40度~150度

8.Use:电子摄影：通电；手机：天线、接地、电池接触。

DIM	TOL	DIM	TOL
X.		X°	3°
X.X	±0.20	X.X°	
X.XX	±0.15	X.XX°	
X.XXX	±0.10	X.XXX°	

Spring Probe

深圳市泰科汉泽精密电子有限公司

Tyco Hanconn Precision Electronics

DRAW NO.		DATE	MATERIAL:Brass C3604	DRAW NAME: SEE TABLE
DESIGN:	譚立強	2012.02.13	FINISH:Au1~3u",Ni,80~120u"	
CHECK:			FILE:	
REVIEW:			P/N:SEE TABLE	
			REV. A0 / SCALE N/A	UNIT: mm / SHEET: 1/1